

SHIPPING & HANDLING INFORMATION PERC Series



Container Ft. 53' | Double Stack

MISSION SOLAR ENERGY

Pallet	72-Cell	66-Cell	60-Cell
26 Panels	MSExxxSX6W, MSExxxSX6Z	MSExxxSX5R	MSExxxSX5T, MSExxxSX5K
Weight	1450 lbs.	1356 lbs.	1263 lbs.
Height	47.56 in	47.56 in	47.56 in
Length	83.75 in	77 in	70.25 in
Width	46 in	46 in	46 in

Product	Container Ft	Ship to	Pallets	Panels	
72-Cell	53'	Most States	28	728	420 W
					305.76 kW
66-Cell	53'	Most States	30	780	380 W
					296.40 kW
60-Cell	53'	Most States	34	884	345 W
					304.98 kW
		California	25	650	273.00 kW
		California	26	676	256.88 kW
		California	28	728	251.16kW

COMPLETE PALLET



EXPLODED PALLET



STORAGE TRANSPORT INSTRUCTIONS



Use caution when moving modules around warehouse or job site. Do not exceed rated load capacity of forklift. Only transport a double-stacked pallet if it is well aligned. Do not collide with other objects while transporting modules. Only use fork lifts with long forks (at least 72" or 6') to move the pallets.



Fragile! Modules should be handled carefully. Do not place modules roughly on hard surface or on their corners. Do not drag modules over each other when unstacking.



Do not use forklift truck on glass side.



The package must always be transported, handled and stored in such a way that the arrows always point upwards.



Do not step or stand on modules. Do not place any objects on modules.



The cardboard sleeve and package materials are recyclable.



Package and modules should be protected from excessive moisture (rain, snow, etc.) and must accordingly be stored under cover. If package and modules cannot be stored in warehouses or sheds, they must be carefully covered with tarpaulins.



Never stack more than 2 pallets high. Double-stacked pallets need to have anti-slip pads between pallets.



Use two people when unpacking modules from pallet. When handling modules always use both hands and safety gloves.